

## Stranded Copper Cable (Tinned)

Kingsmill **Stranded Copper Cable (Tinned)** is used where extra corrosion protection is required.

STRANDING No./DIA (mm)**	NOMINAL DIAMETER (mm)	CSA (mm <sup>2</sup> )	WEIGHT (kg/m)	PART NO.
7 / 1.70	5.10	16	0.15	BSCW016/T
7 / 2.14	6.42	25	0.23	BSCW025/T
7 / 2.52	7.56	35	0.32	BSCW035/T
19 / 1.78	8.90	50	0.43	BSCW050/T
19 / 2.14	10.70	70	0.62	BSCW070/T
19 / 2.52	12.60	95	0.86	BSCW095/T
37 / 2.03	14.21	120	1.09	BSCW120/T
37 / 2.25	15.75	150	1.33	BSCW150/T
37 / 2.52	17.64	185	1.67	BSCW185/T
61 / 2.25	20.25	240	2.20	BSCW240/T
61 / 2.52	22.68	300	2.76	BSCW300/T
61 / 2.85	25.65	400	3.53	BSCW400/T

**Material:** Tinned soft drawn stranded copper cable

\*\*Stranding may vary

**Standard:** BS:EN 60228



## Galvanised Stranded Conductor

Kingsmill **Galvanised Stranded Conductor** is suitable for BS62305 internal foundation earthing rings.

STRANDING NO./DIA (mm)**	NOMINAL DIAMETER (mm)	CSA (mm <sup>2</sup> )	WEIGHT (kg/m)	PART NO.
19/2	10.00	78.55	0.50	GSC10

**Material:** Galvanised steel

\*\*Stranding may vary

**Standard:** BS:EN 12385-4:2002 & A1:2008 Steel Wire Ropes DIN 3053

