

Heavy Duty Metallic Cable Saddles

Heavy Duty Metallic Cable Saddles are suitable for use in both Lightning Protection and Earthing Systems.

Use with bare solid and stranded copper conductor

CONDUCTOR CSA (mm ²)	CONDUCTOR DIA (approx mm)	CONDUCTOR TYPE	WEIGHT (kg)	PART NO.
50	8	Bare solid copper	0.100	HDSC08
16	5.1	Bare stranded copper	0.105	HDCS16
25	6.42	Bare stranded copper	0.105	HDCS25
35	7.56	Bare stranded copper	0.105	HDCS35
50	8.9	Bare stranded copper	0.100	HDCS50
70	10.7	Bare stranded copper	0.100	HDCS70
95	12.6	Bare stranded copper	0.107	HDCS95
120	14.21	Bare stranded copper	0.107	HDCS120
150	15.75	Bare stranded copper	0.215	HDCS150
185	17.64	Bare stranded copper	0.205	HDCS185
240	20.25	Bare stranded copper	0.300	HDCS240
300	22.68	Bare stranded copper	0.290	HDCS300
400	25.65	Bare stranded copper	0.285	HDCS400


Material: High copper content alloy



FIXINGS
1 x CSK 1½ x No.10 woodscrew (BCSW1.5-10) + plug (PP10) not included



[SEE PAGE FIT:20](#)



Use with PVC insulated copper cable

CONDUCTOR CSA (mm ²)	CONDUCTOR DIA (approx mm)	CONDUCTOR TYPE	WEIGHT (kg)	PART NO.
16	7.10	PVC insulated copper cable	0.105	HDCS16INS
25	8.90	PVC insulated copper cable	0.100	HDCS25INS
35	9.95	PVC insulated copper cable	0.100	HDCS35INS
50	11.70	PVC insulated copper cable	0.110	HDCS50INS
70	13.35	PVC insulated copper cable	0.115	HDCS70INS
95	15.60	PVC insulated copper cable	0.215	HDCS95INS
120	17.20	PVC insulated copper cable	0.205	HDCS120INS
150	19.10	PVC insulated copper cable	0.205	HDCS150INS
185	21.30	PVC insulated copper cable	0.295	HDCS185INS
240	24.30	PVC insulated copper cable	0.285	HDCS240INS
300	27.05	PVC insulated copper cable	0.280	HDCS300INS
400	30.35	PVC insulated copper cable	0.275	HDCS400INS

Material: High copper content alloy



FIXINGS
1 x CSK 1½ x No.10 woodscrew (BCSW1.5-10) + plug (PP10) not included



[SEE PAGE FIT:20](#)