

Pyramid Holdfasts

Supplied filled with concrete. Lip around the base enables building in to bitumen type roofs.

| CONDUCTOR DIA (mm) | CONDUCTOR TYPE | FIXING SCREW | CLIP PROVISION | WEIGHT (kg) | PART NO. |
|--------------------|----------------|--------------|----------------|-------------|----------|
| 8 | Bare | - | x 2 | 1.00 | PHFB08X2 |
| 8 | Bare | - | x 1 | 0.98 | PHFB08 |
| 10 | PVC Covered | - | x 1 | 0.98 | PHFB10 |
| Universal | Universal | M6 | x 1 | 0.98 | PHFBM6 |

Material: Polyethylene
Standard: BS:EN 62561-1, Class H



PHFB08 + PHFB10



PHFBM6



PHFB8X2



APPLICATION

COMPONENT ASSEMBLY:

- PHFBM6 + Non-metallic DC Clip = Assembly with copper rod
- PHFBM6 + Metallic DC Clip = Assembly with copper rod
- PHFBM6 + Metallic Cable Saddles = Assembly with copper rod
- PHFBM6 + Square Clamp = Assembly with copper rod
- PHFBM6 + Square Clamp = Assembly with copper rod

Clip/Clamps NOT included - must be ordered separately.