

Couplings (Copperbond Earth Rods)

Kingsmill **Earth Rod Couplings** are counter-bored and of sufficient length to ensure that **Earth Rod** threads are completely enclosed within the coupling. Manufactured from high strength, high copper content alloy to ensure adequate strength and corrosion resistance.

| DESCRIPTION | LENGTH (mm) | BODY DIAMETER ACROSS FLATS (mm) | WEIGHT (kg) | PART NO. |
|-----------------------|-------------|---------------------------------|-------------|----------|
| Rod Coupling 5/8" UNC | 68 | 22 | 0.08 | COUP16 |
| Rod Coupling 3/4" UNC | 79 | 24 | 0.14 | COUP20 |

Material: High Copper Content Alloy
Standard: BS 7430, BS:EN 62561-2: 2012

| DESCRIPTION | LENGTH (mm) | ACROSS FLATS (mm) | WEIGHT (kg) | PART NO. |
|----------------------------------|-------------|-------------------|-------------|-----------|
| 16mm Rod Coupling 5/8" UNC (HEX) | 68 | 20 | 0.11 | COUP16HEX |
| 20mm Rod Coupling 3/4" UNC (HEX) | 80 | 25 | 0.17 | COUP20HEX |

Material: High Copper Content Alloy
Standard: BS:EN 62561-2: 2012

| DESCRIPTION | LENGTH (mm) | BODY DIA. (mm) | WEIGHT (kg) | PART NO. |
|-------------------|-------------|----------------|-------------|----------|
| 5/8" Rod Coupling | 80 | 25 | 0.20 | COUP16S |

Material: Silicon Aluminium Bronze

