

Free-Standing Air Terminals

Free-Standing Air Terminals are suitable for wind speeds ranging from 93 kmph to 258 kmph.

PART NUMBER	MAST HEIGHT (B) (m)	TOTAL HEIGHT(A) (mm)	NO OF BLOCKS	WIND LOADING (kmph)	MPH	TOTAL WEIGHT (kg)
KM68013009	3	3215	3	155	248	59.76
KM68023009	3	3300	6	213	341	107.76
KM68033009	3	3385	9	258	413	155.76
KM68013509	3.5	3715	3	116	186	61.33
KM68023509	3.5	3800	6	159	254	109.33
KM68033509	3.5	3885	9	192	307	157.33
KM68014009	4	4215	3	116	186	61.61
KM68024009	4	4300	6	159	254	109.61
KM68034009	4	4385	9	192	307	157.61
KM68014509	4.5	4715	3	93	149	62.83
KM68024509	4.5	4800	6	127	203	110.83
KM68034509	4.5	4885	9	153	245	158.83
KM68044509	4.5	4970	12	175	280	206.83
KM68015009	5	5215	3	93	149	63.11
KM68025009	5	5300	6	127	203	111.11
KM68035009	5	5385	9	153	245	159.11
KM68045009	5	5470	12	175	280	207.11
KM68025509	5.5	5800	6	106	170	112.33
KM68035509	5.5	5885	9	127	203	160.33
KM68045509	5.5	5970	12	146	234	208.33
KM68055509	5.5	6055	15	149	238	256.33
KM68026009	6	6300	6	106	170	112.61
KM68036009	6	6385	9	127	203	160.61
KM68046009	6	6470	12	146	234	208.61
KM68056009	6	6555	15	149	238	256.61
KM68026509	6.5	6800	6	97	155	113.83
KM68036509	6.5	6885	9	117	187	161.83
KM68046509	6.5	6970	12	133	213	209.83
KM68056509	6.5	7055	15	140	224	257.83
KM68027009	7	7300	6	97	155	114.11
KM68037009	7	7385	9	117	187	162.11
KM68047009	7	7470	12	133	213	210.11
KM68057009	7	7555	15	140	224	258.11
KM68038009	8	8385	9	101	162	162.67
KM68048009	8	8470	12	116	186	210.67
KM68058009	8	8555	15	122	195	258.67

Each **Free-Standing Air Terminals** is manufactured from 16mm diameter aluminium, for lightness, and supplied with:

- 1 x 40mm diameter Aluminium Mast
- 1 x Aluminium Couplers
- 1 x Stainless Steel Tripod Base
- 1 x Steel Threaded Mounting Pin
- 1 x Circular Concrete Mounting Blocks
- 1 x Mounting Block Covers
- 1 x Mounting Bracket

Mounting Bracket is used to connect the Air Terminal to the roof conductor.

The supplied **Mast to Roof Conductor Connector** and **Mounting Bracket** is suitable for either copper or aluminium 8mm or 25 x 3mm conductors.

The supplied **Mounting Block Covers** help to protect the waterproof roof covering from mechanical damage.

The foldable **Stainless Steel Tripod Base** makes for easy handling and lower delivery costs. Manufactured box section, the base has great rigidity and is resistant to corrosion. Being foldable, the base is easy to carry and transport which means lower freight costs.

